



**NOTES:**

1. TYPE 2 DRIVEWAY APRON TO BE USED WITH OFFSET SIDEWALK UNLESS 5 FOOT SURFACE WITH 1.5% MAXIMUM BYPASS IS PROVIDED. (SEE DRIVEWAY APRON BYPASS DETAIL C-5.2.6).
2. COMMERCIAL DRIVEWAYS TO HAVE #4 REBAR AT 18 INCHES ON CENTER EACH WAY EXTENDED INTO GUTTER PAN UNLESS OTHERWISE APPROVED BY THE CITY ENGINEER.
3. IF EXPANSION JOINTS EXIST WITHIN 4 FEET OF DRIVEWAY, REMOVE SIDEWALK, CURB AND GUTTER TO THAT JOINT.
4. DRIVEWAY APRONS SHALL BE CONSTRUCTED IN COMPLIANCE WITH STANDARD DETAILS C-5.1.1 AND C-5.2.1.

NO.	REVISION	DATE	STANDARD DETAIL FOR PUBLIC WORKS CONSTRUCTION	SECTION
1	EXPANSION JT	9/17	<b>P.C.C. DRIVEWAY APRON TYPE 2</b>	CARSON CITY
				DRAWING NO. C-5.2.4
				DATE SEP 2017
APPROVED BY:		9/17		